


SL41


SL41 Solar 60W / 80W / 100W
(Supplied With 3M, 4M, 5M or 6M Column)



Asymmetric optical technology allows light to be directed forwards.



IES and lighting distribution data available for 20W, 30W, and 40W Models.



Utilizes super-efficient high-output SMD LED technology.



Complete 3D lighting renderings available for your application.

This compact, all-in-one, integrated, solar area light is offered in 60W, 80W or 100W LED power versions and includes a choice of 3M, 4M, 5M, or 6M column. This fitting features a choice of three different user/installer selectable operating modes. Programmed using an IR remote control (included). The solar panel is integrated into the top of the fitting and the LEDs are motion sensor are on the underside. Attaches to the top of a 76mm OD column or to the side (using an optional support arm). Choice of root mount or flange mount columns available.



Free Delivery*
UK and Europe ✓

Lowest Price*
Guarantee ✓

Lifetime*
Tech Support ✓

24 Month*
Product Warranty ✓

No Hassle*
Returns ✓

4 Old Park Lane • London • W1K 1QW • Great Britain
Phone: 020 7873 2262 • Fax: 020 7806 8372

www.solarilluminations.co.uk • sales@solarilluminations.co.uk

*SUBJECT TO OUR TERMS & CONDITIONS, AND RETURNS POLICY



SL41

SL41 60W / 80W / 100W
(Supplied With 3M, 4M, 5M or 6M Column)



LUMINAIRE

- Choice of 60W, 80W, or 100W LED power options
- At full output the 60W lamp emits 6,500 lumens, 80W emits 8,500 lumens, and the 100W emits 10,500 lumens
- 5,500~6,000K LED colour temperature
- Three user selectable operating modes and dimming
- Intergated PIR/motion detector for use with some of the operating modes
- IR remote control included (for mode programming)
- Aluminium construction
- IP65 rating
- Fitting attaches to the top of the column or to the side (using an option support arm)
- Dimensions approx. 115cm x 33cm x 10cm

SOLAR PANEL

- 60W model has an integrated a 64W solar panel
- 80W model has an integrated 85W solar panel
- 100W model has an integrated 102W solar panel
- Glass covered solar panel is built into the top of the fitting

COLUMN

- Choice of 3M, 4M, 5M or 6M column
- Column diameter is 76mm OD
- Column type is galvanised steel, root mount or flange mount options
- The 3M, 4M and 5M root mount column has approx. 75cm for burial
- The 6M root mount column has approx. 100cm for burial
- Flange mount column (for surface type installations) includes an anchor kit and template

BATTERY

- Lithium battery pack pre-installed within unit
- Long lifespan battery is replaceable when required
- 60W model supplied with a 12.8V 302 WH battery
- 80W model supplied with a 12.8V 403 WH battery
- 100W model supplied with a 12.8V 502 WH battery

CHARGE CONTROL

- Internal battery over-charge and dis-charge protection
- Automatic day/night detection, on at dusk, off at dawn

Free Delivery* ✓
UK and Europe

Lowest Price* ✓
Guarantee

Lifetime* ✓
Tech Support

24 Month* ✓
Product Warranty

No Hassle* ✓
Returns

4 Old Park Lane • London • W1K 1QW • Great Britain

Phone: 020 7873 2262 • Fax: 020 7806 8372

www.solarilluminations.co.uk • sales@solarilluminations.co.uk

*SUBJECT TO OUR TERMS & CONDITIONS, AND RETURNS POLICY